


<b>Level of expertise required</b>	High
<b>Synergies with other indicators</b>	
<b>Connection with SDGs</b>	11
<b>Opportunities for participatory data collection</b>	
<b>Additional information</b>	
<b>References</b>	



A = Main entry to wood  
 B = Urban centre  
 C = Urban centre

Blue line = Shortest road network distance

### 14.17 Natural and cultural sites made available

**Project Name:** PHUSICOS (Grant Agreement no. 776681)

**Author/s and affiliations:** Gerardo Caroppi<sup>1,2</sup>, Carlo Gerundo<sup>2</sup>, Francesco Pugliese<sup>2</sup>, Maurizio Giugni<sup>2</sup>, Marialuce Stanganelli<sup>2</sup>, Farrokh Nadim<sup>3</sup>, Amy Oen<sup>3</sup>

<sup>1</sup> Aalto University, Department of Built Environment, Espoo, Finland (gerardo.caroppi@aalto.fi)

<sup>2</sup> University of Naples Federico II (UNINA), Department of Civil, Architectural and Environmental Engineering, Naples, Italy

<sup>3</sup> Norwegian Geotechnical Institute (NGI), Oslo, Norway

Accessibility of Natural and Cultural Sites	Place Regeneration
<b>Description and justification</b>	A new infrastructure, implemented in a rural landscape in order to achieve a risk reduction, could also ensure the accessibility to natural and cultural sites previously isolated.

<b>Definition</b>	This Indicator will be equal to 0 in the Baseline Scenario and will be assessed in the Design Scenarios (e.g., NBS Scenario, Hybrid Scenario, Grey Scenario) computing the size of natural and/or cultural sites, in terms of square kilometres, that were previously not accessible and now are free from any hazard and dedicated to recreational activities.
<b>Strengths and weaknesses</b>	It is easy to be estimated and rapidly provides information concerning the benefits achievable in terms of landscape perception.
<b>Measurement procedure and tool</b>	The indicator is equal to the size of the parts of the cultural and natural site in the study area that were previously isolated and that are made accessible to people by the project since they are free from any hazard. Given the vector data of the project and of risk map, common GIS software tools allow calculating these areas.
<b>Scale of measurement</b>	km <sup>2</sup>
<b>Data source</b>	Project team
<b>Required data</b>	Project layout map (vector data); Hazard map
<b>Data input type</b>	Maps; Vectorial data
<b>Data collection frequency</b>	
<b>Level of expertise required</b>	Medium
<b>Synergies with other indicators</b>	
<b>Connection with SDGs</b>	3
<b>Opportunities for participatory data collection</b>	
<b>Additional information</b>	
<b>References</b>	